



Rev. 03-12-2020

## PPP-CWP

### PIT CUSHION WELD PLATES

It is highly recommended to bolt plate to Pit Cushion for proper positioning before welding. ½ inch holes allow welding access to center area of repair for added strength.



Rev. 03-12-2020

## PPP-CWP

### PIT CUSHION WELD PLATES

It is highly recommended to bolt plate to Pit Cushion for proper positioning before welding. ½ inch holes allow welding access to center area of repair for added strength.



Rev. 03-12-2020

## PPP-CWP

### PIT CUSHION WELD PLATES

It is highly recommended to bolt plate to Pit Cushion for proper positioning before welding. ½ inch holes allow welding access to center area of repair for added strength.



Rev. 03-12-2020

## PPP-CWP

### PIT CUSHION WELD PLATES

It is highly recommended to bolt plate to Pit Cushion for proper positioning before welding. ½ inch holes allow welding access to center area of repair for added strength.



Rev. 03-12-2020

## PPP-CWP

### PIT CUSHION WELD PLATES

It is highly recommended to bolt plate to Pit Cushion for proper positioning before welding. ½ inch holes allow welding access to center area of repair for added strength.



Rev. 03-12-2020

## PPP-CWP

### PIT CUSHION WELD PLATES

It is highly recommended to bolt plate to Pit Cushion for proper positioning before welding. ½ inch holes allow welding access to center area of repair for added strength.



Rev. 03-12-2020

## PPP-CWP

### PIT CUSHION WELD PLATES

It is highly recommended to bolt plate to Pit Cushion for proper positioning before welding. ½ inch holes allow welding access to center area of repair for added strength.



Rev. 03-12-2020

## PPP-CWP

### PIT CUSHION WELD PLATES

It is highly recommended to bolt plate to Pit Cushion for proper positioning before welding. ½ inch holes allow welding access to center area of repair for added strength.