




Rev.02-11-2020

Clapper Adjustment Screw Stabilizer

Part No. **PPP-CASS** - Pkg of 1

Thanks to David Ibanez
Hollywood, CA

*2-3/4" set screw not included



When using existing 3/8-16" adjustment screw (in clapper); loosen jam-nut and rotate bottom of screw into clapper to clean threads at screw-end.

Place jam-nut onto 3/8-16" adjustment screw to a distance as to not interfere with screw seating into PPP-CASS.

Insert 3/8-16" adjustment screw into PPP-CASS. Holding screw-handle, rotate 3/8-16 adjustment screw until screw reaches bottom of threaded portion of PPP-CASS.

Do not attempt to force 3/8-16" adjustment screw beyond bottom of PPP-CASS.

Holding screw-handle, firmly secure jam nut.

Remove side hole screw-handle.

Lubricate bottom of PPP-CASS and adjust lift rods height.



Rev.02-11-2020

Clapper Adjustment Screw Stabilizer

Part No. **PPP-CASS** - Pkg of 1

Thanks to David Ibanez
Hollywood, CA

*2-3/4" set screw not included



When using existing 3/8-16" adjustment screw (in clapper); loosen jam-nut and rotate bottom of screw into clapper to clean threads at screw-end.

Place jam-nut onto 3/8-16" adjustment screw to a distance as to not interfere with screw seating into PPP-CASS.

Insert 3/8-16" adjustment screw into PPP-CASS. Holding screw-handle, rotate 3/8-16 adjustment screw until screw reaches bottom of threaded portion of PPP-CASS.

Do not attempt to force 3/8-16" adjustment screw beyond bottom of PPP-CASS.

Holding screw-handle, firmly secure jam nut.

Remove side hole screw-handle.

Lubricate bottom of PPP-CASS and adjust lift rods height.



Rev. 02-11-2020

Clapper Adjustment Screw Stabilizer

Part No. **PPP-CASS** - Pkg of 1

Thanks to David Ibanez
Hollywood, CA

*2-3/4" set screw not included



When using existing 3/8-16" adjustment screw (in clapper); loosen jam-nut and rotate bottom of screw into clapper to clean threads at screw-end.

Place jam-nut onto 3/8-16" adjustment screw to a distance as to not interfere with screw seating into PPP-CASS.

Insert 3/8-16" adjustment screw into PPP-CASS. Holding screw-handle, rotate 3/8-16 adjustment screw until screw reaches bottom of threaded portion of PPP-CASS.

Do not attempt to force 3/8-16" adjustment screw beyond bottom of PPP-CASS.

Holding screw-handle, firmly secure jam nut.

Remove side hole screw-handle.

Lubricate bottom of PPP-CASS and adjust lift rods height.



Rev. 02-11-2020

Clapper Adjustment Screw Stabilizer

Part No. **PPP-CASS** - Pkg of 1

Thanks to David Ibanez
Hollywood, CA

*2-3/4" set screw not included



When using existing 3/8-16" adjustment screw (in clapper); loosen jam-nut and rotate bottom of screw into clapper to clean threads at screw-end.

Place jam-nut onto 3/8-16" adjustment screw to a distance as to not interfere with screw seating into PPP-CASS.

Insert 3/8-16" adjustment screw into PPP-CASS. Holding screw-handle, rotate 3/8-16 adjustment screw until screw reaches bottom of threaded portion of PPP-CASS.

Do not attempt to force 3/8-16" adjustment screw beyond bottom of PPP-CASS.

Holding screw-handle, firmly secure jam nut.

Remove side hole screw-handle.

Lubricate bottom of PPP-CASS and adjust lift rods height.




Rev. 02-11-2020

Clapper Adjustment Screw Stabilizer

Part No. **PPP-CASS** - Pkg of 1

Thanks to David Ibanez
Hollywood, CA

*2-3/4" set screw not included



When using existing 3/8-16" adjustment screw (in clapper); loosen jam-nut and rotate bottom of screw into clapper to clean threads at screw-end.

Place jam-nut onto 3/8-16" adjustment screw to a distance as to not interfere with screw seating into PPP-CASS.

Insert 3/8-16" adjustment screw into PPP-CASS. Holding screw-handle, rotate 3/8-16 adjustment screw until screw reaches bottom of threaded portion of PPP-CASS.

Do not attempt to force 3/8-16" adjustment screw beyond bottom of PPP-CASS.

Holding screw-handle, firmly secure jam nut.

Remove side hole screw-handle.

Lubricate bottom of PPP-CASS and adjust lift rods height.




Rev. 02-11-2020

Clapper Adjustment Screw Stabilizer

Part No. **PPP-CASS** - Pkg of 1

Thanks to David Ibanez
Hollywood, CA

*2-3/4" set screw not included



When using existing 3/8-16" adjustment screw (in clapper); loosen jam-nut and rotate bottom of screw into clapper to clean threads at screw-end.

Place jam-nut onto 3/8-16" adjustment screw to a distance as to not interfere with screw seating into PPP-CASS.

Insert 3/8-16" adjustment screw into PPP-CASS. Holding screw-handle, rotate 3/8-16 adjustment screw until screw reaches bottom of threaded portion of PPP-CASS.

Do not attempt to force 3/8-16" adjustment screw beyond bottom of PPP-CASS.

Holding screw-handle, firmly secure jam nut.

Remove side hole screw-handle.

Lubricate bottom of PPP-CASS and adjust lift rods height.