



Rev. 02-10-2020

### Cushion Shock Mount Pin Deflector

Part No. **PPP-CSPD**

1 1/2" minimum distance between ball wheel and cushion shock mount edge required.

Remove X washer and pin from shock mount.

Place Pin Deflector onto shock mount. Seat shoulder bolt fully into shock mount and secure with oval "special nut".

Place bowling ball in lift rods and test for clearance. Additional clearance can be obtained by further bending of Pin Deflector if needed.

Warning! To prevent permanent damage to shock mount, never place washers, of any kind, behind shoulder bolt head.



Rev. 02-10-2020

### Cushion Shock Mount Pin Deflector

Part No. **PPP-CSPD**

1 1/2" minimum distance between ball wheel and cushion shock mount edge required.

Remove X washer and pin from shock mount.

Place Pin Deflector onto shock mount. Seat shoulder bolt fully into shock mount and secure with oval "special nut".

Place bowling ball in lift rods and test for clearance. Additional clearance can be obtained by further bending of Pin Deflector if needed.

Warning! To prevent permanent damage to shock mount, never place washers, of any kind, behind shoulder bolt head.



Rev. 02-10-2020

### Cushion Shock Mount Pin Deflector

Part No. **PPP-CSPD**

1 1/2" minimum distance between ball wheel and cushion shock mount edge required.

Remove X washer and pin from shock mount.

Place Pin Deflector onto shock mount. Seat shoulder bolt fully into shock mount and secure with oval "special nut".

Place bowling ball in lift rods and test for clearance. Additional clearance can be obtained by further bending of Pin Deflector if needed.

Warning! To prevent permanent damage to shock mount, never place washers, of any kind, behind shoulder bolt head.



Rev. 02-10-2020

### Cushion Shock Mount Pin Deflector

Part No. **PPP-CSPD**

1 1/2" minimum distance between ball wheel and cushion shock mount edge required.

Remove X washer and pin from shock mount.

Place Pin Deflector onto shock mount. Seat shoulder bolt fully into shock mount and secure with oval "special nut".

Place bowling ball in lift rods and test for clearance. Additional clearance can be obtained by further bending of Pin Deflector if needed.

Warning! To prevent permanent damage to shock mount, never place washers, of any kind, behind shoulder bolt head.



Rev. 02-10-2020

### Cushion Shock Mount Pin Deflector

Part No. **PPP-CSPD**

1 1/2" minimum distance between ball wheel and cushion shock mount edge required.

Remove X washer and pin from shock mount.

Place Pin Deflector onto shock mount. Seat shoulder bolt fully into shock mount and secure with oval "special nut".

Place bowling ball in lift rods and test for clearance. Additional clearance can be obtained by further bending of Pin Deflector if needed.

Warning! To prevent permanent damage to shock mount, never place washers, of any kind, behind shoulder bolt head.



Rev. 02-10-2020

### Cushion Shock Mount Pin Deflector

Part No. **PPP-CSPD**

1 1/2" minimum distance between ball wheel and cushion shock mount edge required.

Remove X washer and pin from shock mount.

Place Pin Deflector onto shock mount. Seat shoulder bolt fully into shock mount and secure with oval "special nut".

Place bowling ball in lift rods and test for clearance. Additional clearance can be obtained by further bending of Pin Deflector if needed.

Warning! To prevent permanent damage to shock mount, never place washers, of any kind, behind shoulder bolt head.

