



INSTALLATION INSTRUCTIONS

PART NUMBER	154-8617
PART DESCRIPTION	PATTERN SMOOTHING BLOCK ASSEMBLY
REV DATE	11/11/2011
MACHINE MODELS	ALL MACHINES WITH SMOOTHER PADS



Basic knowledge of the operation of the lane machine

TOOLS NEEDED:

Phillips Screwdriver

Acetone

Scissors



TECHNICAL NOTE

Please thoroughly read the instructions prior to performing the installation of this assembly.

To avoid any potential problems, if at any time during the process you have a question, stop and contact our Tech Support department at the numbers listed below.

Please visit our growing library of videos to see if these instructions are available!



www.youtube.com/user/KegelBowling81



- Place orders with Distributor
- Maintenance reminders on phone
- Software updates
- How to videos

Take full control of your lane machine at My.kegel.net

Kegel's Lane Maintenance Central:
Within USA - 1-800-280-2695
Outside USA - +1 863-734-0200
via e-mail at LMC@Kegel.net
website www.kegel.net



1. Unscrew the 8-32 x 3/8" screws with lock washer that secure the brush pad top plate in place on top of the smoother assy. Remove plate.
2. Remove the existing blocks from the assembly, being careful not to lose the springs.
3. Install the replacement smoother blocks at this time. Place the (2) springs in the holes in the back of the block. Holding these springs, insert opposite end of springs into the holes in the base block. Holding the blocks down and in, place top plate back onto block and re-install screws to secure.
4. All of the blocks should move freely when re-installed and pivot front to back & side to side. If not, remove blocks in question and trim flush w/ ends of blocks. Clean ends of blocks with Acetone or alcohol if necessary. Re-install.



- Place orders with Distributor
- Maintenance reminders on phone
- Software updates
- How to videos

Take full control of your
lane machine at
My.kegel.net

Kegel's Lane Maintenance Central:
Within USA - 1-800-280-2695
Outside USA - +1 863-734-0200
via e-mail at LMC@Kegel.net
website www.kegel.net

