



## INSTALLATION INSTRUCTIONS

PART NUMBER	154-8864
PART DESCRIPTION	VACUUM HOSE UPDATE KIT
REV DATE	05/04/2005
MACHINE MODELS	KUSTODIAN PLUS



Basic knowledge of the operation of the lane machine

---

### TOOLS NEEDED:

Flathead Screwdriver

Wire Cutters

7/16" wrench



### TECHNICAL NOTE

**Please thoroughly read the instructions prior to performing the installation of this assembly.**

**To avoid any potential problems, if at any time during the process you have a question, stop and contact our Tech Support department at the numbers listed below.**

Please visit our growing library of videos to see if these instructions are available!



[www.youtube.com/user/KegelBowling81](http://www.youtube.com/user/KegelBowling81)



- Place orders with Distributor
- Maintenance reminders on phone
- Software updates
- How to videos

Take full control of your lane machine at  
[My.kegel.net](http://My.kegel.net)

**Kegel's Lane Maintenance Central:**  
**Within USA - 1-800-280-2695**  
**Outside USA - +1 863-734-0200**  
via e-mail at [LMC@Kegel.net](mailto:LMC@Kegel.net)  
website [www.kegel.net](http://www.kegel.net)



1. Remove power from the machine.
2. Lay machine down in the operating position.
3. Remove recovery tank from the machine.
4. Loosen the clamp that attached the lower vacuum hose to the squeegee assembly. Remove the vacuum hose from the squeegee adapter and from the gray elbow. Discard hose. Slide new vacuum hose onto gray elbow. Slip clamp over other end of vacuum hose. Place free end of vacuum hose on the squeegee adapter. Tighten clamp down to secure hose to squeegee assembly.
5. Replace recovery tank.
6. Stand machine up in the transport position.
7. Move around to the bottom of the machine. You will need to remove the ¼” bolt on the right side of the squeegee assembly (save the washers and nut). Insert new ¼” bolt provided, through bottom of squeegee. Slide mount angle provided on new bolt and secure using washers and nut removed earlier. Refer to second picture for proper alignment of angle.
8. Insert tie wrap provided through one of the holes in the top of the angle. Loop tie wrap back around hose and secure tightly. Trim end of tie wrap.



- Place orders with Distributor
- Maintenance reminders on phone
- Software updates
- How to videos

Take full control of your  
lane machine at  
[My.kegel.net](http://My.kegel.net)

**Kegel's Lane Maintenance Central:**  
**Within USA - 1-800-280-2695**  
**Outside USA - +1 863-734-0200**  
via e-mail at [LMC@Kegel.net](mailto:LMC@Kegel.net)  
website [www.kegel.net](http://www.kegel.net)

