



INSTALLATION INSTRUCTIONS

PART NUMBER	153-8410
PART DESCRIPTION	LANE EDGE GUIDE ROLLER
REV DATE	11/7/2011
MACHINE MODELS	ALL



Basic knowledge of the operation of the lane machine

TOOLS NEEDED:

3/16" Allen Wrench

½" Wrench

Blue Thread Locker

Vise



TECHNICAL NOTE

Please thoroughly read the instructions prior to performing the installation of this assembly.

To avoid any potential problems, if at any time during the process you have a question, stop and contact our Tech Support department at the numbers listed below.

Please visit our growing library of videos to see if these instructions are available!



www.youtube.com/user/KegelBowling81



- Place orders with Distributor
- Maintenance reminders on phone
- Software updates
- How to videos

Take full control of your lane machine at My.kegel.net

Kegel's Lane Maintenance Central:
Within USA - 1-800-280-2695
Outside USA - +1 863-734-0200
via e-mail at LMC@Kegel.net
website www.kegel.net



- 1) Using the ½” wrench, loosen & remove the two 5/16-18 x 1” HHCS securing the Guide Roller Mounting Bar to the machine frame panel.
- 2) Place the mounting block in the vise & tighten.
- 3) Using the 3/16” Allen Wrench, loosen & remove the shoulder bolt from the block.
- 4) Replace the defective Guide Roller w/ the new one, making sure it’s installed in the same manner as the old one was removed.
- 5) Place a small amount of blue thread locker on the shoulder bolt threads & screw back into the mounting block. Tighten shoulder bolt completely.
- 6) Secure the mounting block back to the inside of the frame panel using the 5/16-18 x 1” HHCS. Tighten completely.



- Place orders with Distributor
- Maintenance reminders on phone
- Software updates
- How to videos

Take full control of your
lane machine at
My.kegel.net

Kegel's Lane Maintenance Central:
Within USA - 1-800-280-2695
Outside USA - +1 863-734-0200
via e-mail at LMC@Kegel.net
website www.kegel.net

