



Rev. 03-13-2020

PPP-PPGN
“Pozi-Nose”™
(Patent Pending)

Installation Instructions

Clean area of ball wheel

Use cleaners that leave no soap residue (isopropyl alcohol)

Remove Backing and install “Pozi-Nose”™ in front of “Pozi-Grip”™ leading edge

Flat end of “Pozi-Nose”™ should match up with leading edge of “Pozi-Grip”™

Pinsetter should be powered down to prevent injury and premature wear to product



Rev. 03-13-2020

PPP-PPGN
“Pozi-Nose”™
(Patent Pending)

Installation Instructions

Clean area of ball wheel

Use cleaners that leave no soap residue (isopropyl alcohol)

Remove Backing and install “Pozi-Nose”™ in front of “Pozi-Grip”™ leading edge

Flat end of “Pozi-Nose”™ should match up with leading edge of “Pozi-Grip”™

Pinsetter should be powered down to prevent injury and premature wear to product



Rev. 03-13-2020

PPP-PPGN
“Pozi-Nose”™
(Patent Pending)

Installation Instructions

Clean area of ball wheel

Use cleaners that leave no soap residue (isopropyl alcohol)

Remove Backing and install “Pozi-Nose”™ in front of “Pozi-Grip”™ leading edge

Flat end of “Pozi-Nose”™ should match up with leading edge of “Pozi-Grip”™

Pinsetter should be powered down to prevent injury and premature wear to product



Rev. 03-13-2020

PPP-PPGN
“Pozi-Nose”™
(Patent Pending)

Installation Instructions

Clean area of ball wheel

Use cleaners that leave no soap residue (isopropyl alcohol)

Remove Backing and install “Pozi-Nose”™ in front of “Pozi-Grip”™ leading edge

Flat end of “Pozi-Nose”™ should match up with leading edge of “Pozi-Grip”™

Pinsetter should be powered down to prevent injury and premature wear to product