



## INSTALLATION INSTRUCTIONS

PART NUMBER	154-8867 & 154-8867A
PART DESCRIPTION	CLEANER TANK FILTER ASSEMBLY
REV DATE	11/10/2011
MACHINE MODELS	ALL MACHINES



Basic knowledge of the operation of the lane machine

### TOOLS NEEDED:

7/16" Wrench

Rags

Craftsman Cutters (if applicable)



### TECHNICAL NOTE

Please thoroughly read the instructions prior to performing the installation of this assembly.

To avoid any potential problems, if at any time during the process you have a question, stop and contact our Tech Support department at the numbers listed below.

Please visit our growing library of videos to see if these instructions are available!



[www.youtube.com/user/KegelBowling81](http://www.youtube.com/user/KegelBowling81)



- Place orders with Distributor
- Maintenance reminders on phone
- Software updates
- How to videos

Take full control of your lane machine at  
[My.kegel.net](http://My.kegel.net)

**Kegel's Lane Maintenance Central:**  
Within USA - 1-800-280-2695  
Outside USA - +1 863-734-0200  
via e-mail at [LMC@Kegel.net](mailto:LMC@Kegel.net)  
website [www.kegel.net](http://www.kegel.net)



**NOTE: THIS ASSEMBLY IS DESIGNED FOR USE ON SEVERAL VARIOUS CLEANER TANK SET-UPS. IF YOUR CLEANER TANK'S IN-LINE FILTER IS ON THE SIDE OF THE TANK, YOU MAY HAVE TO CUT THE TUBING IN THIS ASSEMBLY. MEASURE YOUR CURRENT FILTER ASSEMBLY AND CUT HOSE(S) TO THE CORRECT SIZE.**

Disconnect power from the lane machine and lay it down in the operating position.

1. Make sure the fluid level in the cleaner tank is as low as possible before removal to prevent leaks or spills in the machine.
2. Loosen and remove both 7/16" fasteners holding the cleaner tank to the machine wall. Set fasteners aside for re-installation of tank assembly. Tilt tank to access the fitting the old filter assy is plugged into
3. Unplug the old filter assy from the tank & hose fittings.
4. Plug the new filter assy into the tank, making sure the hoses are pushed completely into the fittings
5. Re-install cleaner tank in machine.
6. Fill tank w/ enough cleaner so the fluid level is above the filter fitting. Visually check filter & elbows for leaks before completely filling tank.



- Place orders with Distributor
- Maintenance reminders on phone
- Software updates
- How to videos

Take full control of your  
lane machine at  
[My.kegel.net](http://My.kegel.net)

**Kegel's Lane Maintenance Central:**  
**Within USA - 1-800-280-2695**  
**Outside USA - +1 863-734-0200**  
via e-mail at [LMC@Kegel.net](mailto:LMC@Kegel.net)  
website [www.kegel.net](http://www.kegel.net)

